



actual size

Oscillator · TCXO · JT32C

TCXO with HCMOS output · 3.2 x 2.5 mm

- excellent phase noise
- operating temperature range -40 °C ~ +85 °C
- reflow soldering temperature: 260 °C max.
- ceramic/metal package



General Data

type		JT32C
frequency range		4.0 ~ 54.0 MHz
frequency stability	at +25 °C	± 0.5 ppm
	temperature	± 2.5 ppm (others on request)
	aging first year	± 1.0 ppm
	supply voltage	± 0.2 ppm (at V _{DC} ± 5%)
	load change	± 0.2 ppm
	after reflow	± 1.0 ppm
current consumption max.		→ see table 1
supply voltage V _{DC}		2.5 / 2.8 / 3.3 (± 5%)
temperature	operating	-30 °C ~ +75 °C / -40 °C ~ +85 °C
	storage	-40 °C ~ +125 °C
output	rise & fall time	5.0 ns max.
	load max.	15 pF
	current max.	4.0 mA
	low level max.	0.1 x V _{DC}
	high level min.	0.9 x V _{DC}
harmonics distortion max.		-5.0 dBc
symmetry at 0.5 x V _{DC}		45% ~ 55% max.
start-up time max.		10 ms
standby current max.		10 µA
output enable time max.		10 ms
output disable time max.		250 ns
Jitter 1 σ		3.0 ps
phase noise at 10 kHz offset		-145 dBc/Hz

	4 ~ 10 MHz	~ 20 MHz	~ 30 MHz	~ 40 MHz	~ 54 MHz
2.5 V	3.1 mA	3.7 mA	4.2 mA	4.6 mA	5.5 mA
2.8 V	3.4 mA	4.1 mA	4.7 mA	5.2 mA	6.0 mA
3.3 V	4.0 mA	4.8 mA	5.5 mA	6.0 mA	7.0 mA

Enable / Disable Function

pin #1 (e/d control)	pin #3 (output)
open	active
high "1" (V _{IH} ≥ 0.7 V _{DC})	active
low "0" (V _{IL} ≤ 0.3 V _{DC})	high impedance
stop function: <ul style="list-style-type: none"> • oscillator stops • output high impedance 	

Note

4 user pins (e/d, GND, output, V_{DC})
leave the other pins unconnected!

Dimensions

top view

side view

bottom view

pad layout

TCXO
JT32C
1: e/d
2: GND
3: output
4: V_{DC}

pin connection

in mm

Order Information

0	frequency in MHz	—	type	—	frequency stability code	—	operating temp. code	—	supply voltage
Oscillator	4.0 ~ 54.0 MHz		JT32C = TCXO		A = ± 2.5 ppm		G = -30 °C ~ +75 °C K = -40 °C ~ +85 °C		2.5 = 2.5 V 2.8 = 2.8 V 3.3 = 3.3 V

Example: O 16.3680-JT32C-A-K-3.3-LF (Suffix LF = RoHS compliant / Pb free pads)

